

Manual Call Point

230V~ Mains Powered with Rechargeable Battery Back-up

Model MCP401RC

- For use with 2100, 160RC, 140 and 260 Series Smoke, Heat & CO Alarms
- When the front plate is pressed, all interconnected alarms will trigger
- Resettable front plate - does not require replacement glass
- 5 Year Guarantee



Product Description

The MCP401RC is a Manual Call Point that runs on 230V AC mains power. It has built in rechargeable Lithium cells that act as a battery back-up in the event of mains failure. These rechargeable cells are designed to have a ten year life and outlast the life of the unit itself, whilst providing up to 2 months of operation without mains power

Any combination of 2100, 160RC, 140 and 260 Series alarms can be used up to a maximum of 20 units (including the MCP401RC)

Operation

- When the Manual Call Point is activated, it will trigger all alarms causing them to sound
- When the unit is reset (using the key provided) it will automatically cancel the interconnect signal, and the alarms will stop sounding
- The unit uses a flexible plastic front plate to mimic the feel of breaking glass, but resets without the need for replacement



Model MCP401RC

Technical Specification

1. A unique Manual Call Point that mimics the feel of breaking glass whilst offering the benefits of a re-settable operating element.
2. 230VAC Mains powered with tamper proof rechargeable Lithium cells designed to last 10 years (the life of the unit) whilst providing up to 2 months operation in the event of mains failure.
3. Suitable for use with 2100, 160RC, 140 and 260 Series Smoke, Heat and CO alarms (up to a maximum of 20 including the MCP401RC).
4. Easily installed via a 3-core connection - Live, Neutral and Interconnect (the same as the Smoke/Heat/CO alarms), using 0.75mm² or 1.00mm² cable.
5. When the front plate is pressed, a visible warning flag will appear to indicate it has been activated.
6. Simple key to reset the unit (no broken glass).
7. Replacement Key (MCPSK2) available.
8. Supplied with 35mm deep surface mounting box, reset key and all screws and fixings.
9. Dimensions: 85 x 85 x 60mm.
10. Weight inclusive of packaging: 230g.
11. 5 Year Guarantee.
12. Manufactured in Ireland.



Mile End Business Park, Oswestry, Shropshire SY10 8NN

Tel. 0870 758 4000

Fax. 0870 758 4010

www.aico.co.uk

E & OE Our policy is one of continuous improvement.

We reserve the right to amend designs and specifications without prior notice.

MCP401RC DataSht Rev 1 21.12.10

Aico Ltd is a wholly owned subsidiary of Ei Electronics