





Product Description:

BackLite[™] 26W 600 x 600mm Panel

Uniquely lensed LED's have been engineered to ensure maximum light output and complete uniformity. Producing 100lm/W for outstanding energy savings, the TP(a) and UGR19 achievable rated backlit panel is suitable for a wide range of applications including office, education and commercial spaces.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-BLPE6060/40	36	4000	3600	100	110	White	Non Dimmable
AU-BLPE6060/65	36	6500	3600	100	110	White	Non Dimmable
AU-BLPE6060DA/40	36	4000	3600	100	110	White	DALI Dimmable
AU-BLPE6060DA/65	36	6500	3600	100	110	White	DALI Dimmable
AU-BLPE6060V/40	36	4000	3600	100	110	White	1-10V Dimmable
AU-BLPE6060V/65	36	6500	3600	100	110	White	1-10V Dimmable

Line Drawing	Polar Curve	Colour
		White

Feature & Benefits

 No light guide, removing the risk of yellowing • Flicker free driver

Power Factor > 0.9

- PMMA lenses for uniformity of light
- SDCM <5 providing consistent light colour quality

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	50000hrs	Lifetime L80 (Hours)	50000hrs
IK Rating	IK02	Width (mm)	595
Length (mm)	595	Height (mm)	27
Product Type	Panels	Operating Temp. (Min) °C	-25°C
Operating Temp. (Max) °C	40°C		

• UGR19 achievable

• TP(a) rated

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

• Suitable for installation in 15

and 24mm T-bar ceilings

• 5 Year Warranty