






















# Product Description:

Lumi-Fit™ 45W High Performance Dimmable Downlight

The range of triac dimmable Lumi-Fit<sup>TM</sup> commercial downlights deliver up to an impressive 106lm/W. Supplied with remote driver and fitted with an acrylic diffuser to reduce glare and for even light distribution. With multiple wattages and sizes on offer this range meets the needs for countless new commercial applications or an upgrade for compact fluorescent fittings in existing applications.

| SKU Code         | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour | SKU Type       |
|------------------|---------|--------|--------|-------------|------------|---------------|----------------|
| EN-DDLH1045/40   | 45      | 4000   | 4500   | 100         | 100        | Matt White    | Triac Dimmable |
| EN-DDLH1045DA/40 | 45      | 4000   | 4500   | 100         | 100        | Matt White    | DALI Dimmable  |
| EN-DDLH1045V/40  | 45      | 4000   | 4500   | 100         | 100        | Matt White    | 1-10V Dimmable |

Line Drawing



Polar Curve



Matt White

### Product Features:

- Low cost energy saving alternative to compact fluorescent fittings
- Life not affected by frequent switching e.g. when used with occupancy controls
- Triac dimmable as standard
- Plug and play remote driver for easy installation
- DALI version available to order
- IP54 rated
- 1.5kV surge protection
- Passes 850°C glow wire testing
- 3 year warranty

### **Product Specs:**

| Input Voltage            | 200~240V AC |
|--------------------------|-------------|
| Power Factor             | 0.9         |
| Lifetime L70 (hrs)       | 40000       |
| Height (mm)              | 54          |
| Weight (Kg)              | 1.437       |
| Product Type             | Downlights  |
| Operating Temp. (Max) °C | 45°C        |

| Input Frequency          | 50/60HZ |
|--------------------------|---------|
| IP Rating                | IP54    |
| Lamp Base                | None    |
| Overall Diameter (mm)    | 280     |
| Cutout Diameter (mm)     | 260     |
| Operating Temp. (Min) °C | -20°C   |
|                          |         |

## Compliance & Approvals:





























This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.