

Product Description:

Designed to last in a tough environment, the UtiliteXL™ wall pack with cast aluminium base and polycarbonate diffuser is available in standard, microwave sensor, photocell and emergency versions with black housing.

Product Image:




UtiliteXL™ 30W IP65 Wall Pack

Product Features:

- IP65 wall pack with cast aluminium base and polycarbonate diffuser.
- IK10 rating
- Non-dimmable with integrated LED driver
- Suitable for walkways, stairways, general amenity & security areas.
- SEAI: EN-WP103/40 - LIG84989
- 3 year warranty

Line Drawing Image



Product Specs:

Technology	LED	Number of LEDs	60
Luminaire Distribution	Ambient	Lifetime L70 (hrs)	50000
Input Voltage	220~240V AC	Input Frequency	50/60HZ
Dimmable	No	IP Rating	IP65
IK Rating	IK10	Fire Protection	No
Operating Env. Temp. (Min) °C	-20	Operating Env. Temp. (Max) °C	45
Optic Material	PC	Power Factor	0.9
Lamp Base	None	Height (mm)	309
Length (mm)	309	Width (mm)	264
Surge Protection (kV)	1.5	SDCM	6

SKU Table and Ordering

SKU Code	Wattage	Lumens	Lumens/Watt	Colour	Beam Angle	Ra	SDCM
EN-WP103/40	30	2550	85	4000	120	80	6
EN-WP103EM/40	30	2550	85	4000	120	80	6
EN-WP103PH/40	30	2550	85	4000	120	80	6

Compliance & Approvals:



Warranty

This product has a warranty period of 3 Years.

Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.

UK Enlite Sales & Distribution

Apex Park

6 Little Burrow

Welwyn Garden City AL7 4SW

United Kingdom

Tel : +44 (0) 1707 35 18 20