



ARX Anti-Ligature Surface Linear CCT 1500mm White



- Ultra robust anti-ligature surface linear fitting suitable for healthcare, education and external subway/walkway applications
- IK10 and IP54 ratings ensure anti-vandal resistance and suitability for anti-ligature applications
- Intelligently designed 2 part construction means fewer screws when removing and re-attaching front frame, ensuring a quick and easy installation
- CCT selectable between 4000K, 5000K and 6000K and power selectable; offering a choice of 6 outputs in one luminaire

Features

Feature 1	Ultra robust anti-ligature surface linear fitting suitable for healthcare, education and external subway/walkway applications
Feature 2	IK10 and IP54 ratings ensure anti-vandal resistance and suitability for anti-ligature applications
Feature 3	Intelligently designed 2 part construction means fewer screws when removing and re-attaching front frame, ensuring a quick and easy installation
Feature 4	CCT selectable between 4000K, 5000K and 6000K and power selectable; offering a choice of 6 outputs in one luminaire



General Information

Lamp Type	LED
IP Rating	IP65
IK Rating	IK10
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface
OCTO Category	OCTO options available
Warranty (Years)	5
Material	Polycarbonate,Steel

Technical Information

Wattage	14/28/43/57W
Lumens Delivered	1800-7300lm (4000K)
Lm/W	130lm/W (4000K)
Beam Angle	100
CRI	80
CCT	4000/5000/6500K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C - 40°C
Lumen Depreciation	L80 90,000h
Power Factor	0.9



