



AERMLED2/120/CW

Endurance TP(a) 1200x600 Panel Cool White



Features

LED panel suitable for education, commercial and ancillary area applications

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

Surface mounting frame option

Powered by Tridonic

TPa as standard

General Information

Lamp Type	LED
Colour / Finish	White
Bluetooth Enabled	Yes
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 B10 50,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1,195 mm
Width (mm)	595 mm
Depth (mm)	10 mm
Accessories	AERMLD/120/SMF, APRK/120

Technical Information

Wattage	60W
Lumens Delivered	5800lm
Lm/W	96lm/W
Beam Angle	110
CRI	80
CCT	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C
SDCM	6
UGR	20

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:16 AM



