



AERMLED2/120/DL

Endurance TP(a) 1200x600 Panel Daylight



Features

LED panel suitable for education, commercial and ancillary area applications

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

Surface mounting frame option

Powered by Tridonic

TPa as standard

General Information

Lamp Type	LED
Colour / Finish	White
Bluetooth Enabled	Yes
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed, Surface
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L80 B10 50,000h
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1,195 mm
Width (mm)	595 mm
Depth (mm)	10 mm
Accessories	AERMLD/120/SMF, APRK/120

Technical Information

Wattage 60W

Lumens Delivered 5700lm

Lm/W 94lm/W

Beam Angle 110

CRI 80

CCT 6000K

Input 220/240V

Hertz 50/60Hz

Operating Temp -20°C to 40°C

SDCM 6

UGR 20

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:16 AM

