



## AMALED120/CCT

Matrix CCT Linklight 1200mm



### Features

CCT Selectable LED linklight with integral driver suitable for residential and hospitality applications

Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options

Moulded spine fitted with integral switch and fixed diffuser

c/w angled and straight fixing clips

Supplied c/w 1.5m mains power lead

Linkable up to a maximum of twelve fittings

Non-dimmable

## General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L70 B10 25,000h
Warranty (Years)	4
CE Mark	Yes
Length (mm)	1,158 mm
Width (mm)	22.8 mm
Depth (mm)	38.4 mm
Accessories	A250TLL/T5, A500TLL/T5, A1000TLL/T5

# Technical Information

---

<b>Wattage</b>	18W
<b>Lumens Delivered</b>	1800lm (4000K)
<b>Lm/W</b>	102lm/W (4000K)
<b>Beam Angle</b>	100
<b>CRI</b>	80
<b>CCT</b>	3000/4000K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-10°C to 40°C
<b>SDCM</b>	6
<b>UGR</b>	20

---

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:05 AM