



AMALED20/CCT

Matrix CCT Linklight 200mm



Features

CCT Selectable LED linklight with integral driver suitable for residential and hospitality applications

Side mounted switch allows installer the choice of 3000K or 4000K colour temperature options

Moulded spine fitted with integral switch and fixed diffuser

c/w angled and straight fixing clips

Supplied c/w 1.5m mains power lead

Linkable up to a maximum of twelve fittings

Non-dimmable

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Diffuser Rating	Tp(a)
Lifetime (Hrs)	L70 B10 25,000h
Warranty (Years)	4
CE Mark	Yes
Length (mm)	220 mm
Width (mm)	22.8 mm
Depth (mm)	38.4 mm
Accessories	A250TLL/T5, A500TLL/T5, A1000TLL/T5

Technical Information

Wattage	3W
Lumens Delivered	290lm (4000K)
Lm/W	97lm/W (4000K)
Beam Angle	100
CRI	80
CCT	3000/4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C
SDCM	6
UGR	19

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:05 AM

