



APCLEDWL

Parona Graphite



Features

Compact low level circular LED pathway light with downward light spill suitable for residential and hospitality applications

Die-cast aluminium construction with graphite paint finish

Supplied c/w plastic installation box and pre-wired with 1 metre of rubber insulated cable for ease of installation

Non-dimmable

General Information

| | |
|--------------------------------|-------------|
| Lamp Type | LED |
| Colour / Finish | Graphite |
| IP Rating | IP65 |
| IK Rating | IK02 |
| Class Protection | 1 |
| Internal / External | External |
| Surface / Recessed / Suspended | Recessed |
| Lifetime (Hrs) | L70 50,000h |
| Warranty (Years) | 3 |
| CE Mark | Yes |
| Width (mm) | 115 mm |
| Depth (mm) | 131 mm |

Technical Information

| | |
|------------------|---------------|
| Wattage | 3W |
| Lumens Delivered | 70lm |
| Lm/W | 23lm/W |
| Beam Angle | 70 |
| CRI | 80 |
| CCT | 3000/4000K |
| Input | 220/240V |
| Hertz | 50/60Hz |
| Operating Temp | -20°C to 25°C |
| SDCM | 5 |

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:07 AM

