

AULED80D

Unity 80 Downlight Cool White



Features

IP44 compact high performance architectural downlight suitable for commercial, hospitality and retail applications

Die-cast aluminium construction, powder coated and 30° cut-off angle

Mirror finished anodized reflector

Anti-glare design to create visual comfort

Remote driver with plug and play connection

Powered by Tridonic

General Information

Lamp Type	LED
------------------	-----

Colour / Finish	White
------------------------	-------

Bluetooth Enabled	Yes
--------------------------	-----

IP Rating	IP44
------------------	------

IK Rating	IK02
------------------	------

Class Protection	2
-------------------------	---

Bathroom Zone	2
----------------------	---

Internal / External	Internal
----------------------------	----------

Surface / Recessed / Suspended	Recessed
---------------------------------------	----------

Lifetime (Hrs)	L70 50,000h
-----------------------	-------------

Warranty (Years)	5
-------------------------	---

CE Mark	Yes
----------------	-----

Diameter (mm)	90 mm
----------------------	-------

Height (mm)	83 mm
--------------------	-------

Technical Information

Wattage	15W
Lumens Delivered	1200lm
Lm/W	77lm/W
Beam Angle	55
CRI	90
CCT	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C
SDCM	3
UGR	18



