



## AVASLED5/B

Vasco CCT Bi-directional Suspended Linear 1500mm Black



## Features

Aluminium bi-directional suspended pendant suitable for education, commercial and retail applications

Aluminium extruded construction with integral driver

Supplied bi-directional light output as standard with 30% upward light and 70% downward light ratio (directional only option can be selected if required)

Opal diffuser provides optimal light uniformity

Selectable CCT between 3000K,4000K and 6000K output

Pre-wired with 1.5 metre cable

Adjustable suspension points c/w suspension kit

1-10V dimmable as standard

## General Information

---

<b>Lamp Type</b>	LED
<b>Colour / Finish</b>	Black
<b>IP Rating</b>	IP20
<b>Class Protection</b>	1
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Surface,Suspended
<b>Lifetime (Hrs)</b>	L90 36,000h
<b>Warranty (Years)</b>	3
<b>CE Mark</b>	Yes
<b>Length (mm)</b>	1,504 mm
<b>Width (mm)</b>	56 mm
<b>Height (mm)</b>	75 mm
<b>Accessories</b>	AVASLED/LC, AVASLED/90, AVASLED/90/B

---

# Technical Information

<b>Wattage</b>	60W
<b>Lumens Delivered</b>	6300lm (4000K)
<b>Lm/W</b>	105lm/W (4000K)
<b>Beam Angle</b>	105
<b>CRI</b>	80
<b>CCT</b>	3000/4000/6500K
<b>Input</b>	220/240V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-20°C to 45°C
<b>SDCM</b>	6
<b>UGR</b>	23

Datasheet generated from <https://onetimepim.com> last updated Thursday, October 6, 2022 8:27:15 AM



