



## Z LED ECO Highbay 1 Cool White



- Sleek and robust LED low/high bay for industrial applications and ancillary areas
- Die-cast powder coated construction and heatsink for optimum thermals and performance
- Lensed diffuser design helps to control the beam angle, offering better light distribution
- High efficiency up to 120lm/w
- Integral on-board driver reduces the overall size and weight of product, resulting in a slim, lightweight and easy to install unit
- Installation eye-bolt supplied as standard
- Alternative installation options by means of drop rods, jack chain and catenary wire.
- IP65 and IK06 ratings
- Pre-wired with 1M of H05RN-F cable for ease and speed of installation

### Features

Feature 1	Sleek and robust LED low/high bay for industrial applications and ancillary areas
Feature 2	Die-cast powder coated construction and heatsink for optimum thermals and performance
Feature 3	Lensed diffuser design helps to control the beam angle, offering better light distribution





Feature 4	High efficiency up to 120lm/w
Feature 5	Integral on-board driver reduces the overall size and weight of product, resulting in a slim, lightweight and easy to install unit
Feature 6	Installation eye-bolt supplied as standard
Feature 7	Alternative installation options by means of drop rods, jack chain and catenary wire.
Feature 8	IP65 and IK06 ratings
Feature 9	Pre-wired with 1M of H05RN-F cable for ease and speed of installation
General Information	
Lamp Type	LED
IP Rating	IP66
IK Rating	IK09
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface,Suspended
Warranty (Years)	3
Material	Aluminium
Technical Information	
Wattage	100W
Lumens Delivered	11000lm
Lm/W	120lm/W
Beam Angle	90
CRI	80
CCT	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-45°C - 45°C
Lumen Depreciation	L80 54,000h

