

AZLEDPLUS/1

Z LED PLUS 75W Cool White



Features

Industry leading super high efficiency (200 lm/W) robust LED low/high bay for industrial, commercial and retail applications

Overall power consumptions reduced to offer traditional light output comparable to 100W, 150W and 200W but offering more accelerated energy savings

High specification IP65 and IK08 ratings

Die-cast powder coated construction and heatsink for optimum thermals and performance

Alternative installation options by means of drop rods, jack chain and catenary wire.

Bracket accessories available for ceiling or wall mounting

Pre-wired with 3M of H07RN-F cable for ease and speed of installation

1-10V dimmable as standard



General Information

Lamp Type	LED
Colour / Finish	Black
Dimmable	Yes
Bluetooth Enabled	Yes
IP Rating	IP65
IK Rating	IK08
Class Protection	1
Internal / External	Internal / External
Surface / Recessed / Suspended	Surface,Suspended
Lifetime (Hrs)	L90 B10 50,000h
Warranty (Years)	6
CE Mark	Yes
Diameter (mm)	265 mm
Height (mm)	152 mm
Accessories	AZLEDPLUS/REF1, AZLEDPLUS/FB1



Technical Information

Wattage	75W
Lumens Delivered	15000lm
Lm/W	200lm/W
Beam Angle	110
CRI	70
ССТ	4000K
Input	220/240V
Hertz	50/60Hz
Operating Temp	-35°C to 50°C
SDCM	4
UGR	30

Datasheet generated from https://onetimepim.com last updated Thursday, October 6, 2022 8:27:12 AM

