

Product Code: AU-LED1012CV

### Features & Applications

- Registered Community Design 001886730 For the supply of low voltage LED lamps
- 12V DC output Overload protection Short circuit protection Thermal protection
- Secondary wiring terminals - 3 outputs Loop-in, loop-out primary wiring terminals
- Integrated earth terminal for earth continuity No junction box required 1.0kV SURGE PROTECTION – EN 61547 Safety compliance – EN 61347 EMC compliance – EN 55015, EN 61000, EN 61547 Non-dimmable Parallel wiring only 3 Year guarantee



### Full Description

**10W 12V DC NON-DIMMABLE CONSTANT VOLTAGE LED DRIVER**

### Approvals



### Specifications

Input Voltage (V)	100-264V AC 50/60Hz
Output Voltage (V)	12V DC V
Nominal Power (VA)	10W VA
Line Current (A)	0.060 A
Sec Current (A)	0.830 A
Power Factor	0.980
Max Ambient Temp (deg. C)	50 deg. C
Max Case Temp (deg. C)	80 deg. C
Case Colour	White Blue Cap
Case Material	Polycarbonate
Protection Class	Class 2
Self Monitoring	<input type="checkbox"/>
Dimmable	<input type="checkbox"/>
Thermal Protection	Thermal Fuse
Length (mm)	122 mm
Width (mm)	40 mm
Height (mm)	24 mm
Surge Protection (W)	1500 W
Short Circuit Protection	<input checked="" type="checkbox"/>
Overload Protection	<input checked="" type="checkbox"/>
Soft Start	<input checked="" type="checkbox"/>
Primary Connection Type	Screw Terminal - 2 Pairs
Secondary Connection Type	Screw Terminal - 3 Pairs
Incoming Protection	Anti Fire Resistor
Colour	Clear Blue
Guarantee	3 Years
Product Weight	0.078 Kg

*'Passionate about Lighting'*