

**Product Features:**

- IP66 LED bulkhead not affected by frequent switching
- IK10 polycarbonate body and diffuser for maximum vandal resistance
- Rear entry access wiring compartment allows for easy installation
- Interchangeable eyelid bezel accessory available
- Separate 20mm conduit side entries
- Wall or ceiling mounted - accessories included
- Emergency and microwave options available
- Adjustable light detector from 2-50 lux
- Adjustable hold time 5 seconds to 30 minutes
- 1.5kV surge protection
- 3 year warranty

**Product Image:**




Orbital™ 25W Polycarbonate IP66 Round LED Bulkhead


**Product Specs:**

<b>Technology</b>	LED	<b>Lamp Base</b>	None
<b>Input Voltage</b>	220~240V AC	<b>LED Chip</b>	2835
<b>Number of LEDs</b>	136	<b>Positional Adjustment</b>	Fixed
<b>Input Frequency</b>	50/60HZ	<b>Lifetime L70 (hrs)</b>	25000
<b>Power Factor</b>	0.9	<b>Dimmable</b>	No
<b>Luminaire Distribution</b>	Direct	<b>Positional Adjustment</b>	Fixed
<b>IP Rating</b>	IP66	<b>IK Rating</b>	IK10
<b>SDCM</b>	5	<b>Operating Temp</b>	40°C
<b>Optic Material</b>	PC	<b>Overall Diameter (mm)</b>	300
<b>Recess Depth (mm)</b>	365	<b>Weight (Kg)</b>	1.624

**Line Drawing**



**Polar Curve**



**SKU Table and Ordering:**

Cat No. (SKU Code)	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour
EN-BH25BLK/40	25	4000	1800	72	120	Black
EN-BH25BLK/40EM	27	4000	1800	66.67	120	Black
EN-BH25BLK/40EMR	27	4000	1800		120	Black
EN-BH25BLK/40MS	25	4000	1800	72	120	Black
EN-BH25BLK/40MSC	25	4000	1800	72	120	Black
EN-BH25W/40	25	4000	1800	72	120	White
EN-BH25W/40EM	27	4000	1800	66.67	120	White
EN-BH25W/40EMR	27	4000	1800		120	White
EN-BH25W/40MS	25	4000	1800	72	120	White
EN-BH25W/40MSC	25	4000	1800	72	120	White

**Compliance & Approvals:**



**Warranty:**

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.