

**Product Features:**

- Multiple sizes and wattages available to suit all new and retrofit installation lighting requirements
- ThermoTec™ technology utilises a combination of highly efficient LED light source, aluminium heat sinking and thermoplastic material for longer life and consistent performance
- Compact integrated driver enables easy installation
- Life not affected by frequent switching e.g. when used with occupancy controls
- Pre-wired with 500mm 2 core cable
- 1.5kV surge protection
- 3 year warranty

**Product Image:**




Uni-Fit™ 240V 15W Dimmable Integrated IP44 LED Downlight


**Product Specs:**

|                               |        |                              |             |
|-------------------------------|--------|------------------------------|-------------|
| <b>Technology</b>             | LED    | <b>Input Voltage</b>         | 220~240V AC |
| <b>LED Chip</b>               | 2835   | <b>Positional Adjustment</b> | Fixed       |
| <b>Input Frequency</b>        | /50HZ  | <b>Lifetime L70 (hrs)</b>    | 25000       |
| <b>Power Factor</b>           | 0.9    | <b>Dimmable</b>              | Yes         |
| <b>Luminaire Distribution</b> | Accent | <b>Positional Adjustment</b> | Fixed       |
| <b>IP Rating</b>              | IP44   | <b>SDCM</b>                  | 6           |
| <b>Overall Diameter (mm)</b>  | 150    | <b>Cutout Diameter (mm)</b>  | 120         |
| <b>Recess Depth (mm)</b>      | 70     | <b>Weight (Kg)</b>           | 0.254       |

**Line Drawing**



**Polar Curve**



**SKU Table and Ordering:**

| Cat No.(SKU Code) | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|-------------------|---------|--------|--------|-------------|------------|---------------|
| EN-DDL15/40       | 15      | 4000   | 1100   | 73.33       | 100        | White         |

**Compliance & Approvals:**



**Warranty:**

This product has a guarantee period of . Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.