

Product Features:

- EnFiniti™ edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- Fibre based insulation coverable - up to 300mm
- Integrated driver with new push fit loop in/out terminals suitable for use with solid or stranded cable for easy installation
- Super slim interchangeable bezels for fixed version provide a high end sleek finish. Bezel included with adjustable version
- IP65 with the appropriate bezel (sold separately)
- Tested in 30, 60 and 90-minute fire rated ceilings
- 3 year warranty

Product Image:




E8™ Adjustable 8W Dimmable Fire Rated LED Downlight


Product Specs:

| | | | |
|-------------------------------|------------|----------------------------------|-------------|
| Technology | LED | Input Voltage | 220~240V AC |
| LED Chip | 3030 | Number of LEDs | 9 |
| Positional Adjustment | Adjustable | Positional Adjustment (°) | 20 |
| Input Frequency | /50HZ | Lifetime L70 (hrs) | 25000 |
| Power Factor | 0.85 | Dimmable | Yes |
| Luminaire Distribution | Accent | Positional Adjustment | Adjustable |
| IP Rating | IP20 | Fire Protection | Yes |
| Acoustic Rated | Yes | SDCM | 6 |
| Optic Material | PMMA | Overall Diameter (mm) | 98 |
| Cutout Diameter (mm) | 85 | Recess Depth (mm) | 100 |
| Weight (Kg) | 0.365 | | |

Line Drawing



Polar Curve



SKU Table and Ordering:

| Cat No.(SKU Code) | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|-------------------|---------|--------|--------|-------------|------------|-----------------|
| EN-DE82MW/30 | 8 | 3000 | 610 | 76.25 | 60 | Matt White |
| EN-DE82MW/40 | 8 | 4000 | 640 | 80 | 60 | Matt White |
| EN-DE82PC/30 | 8 | 3000 | 610 | 76.25 | 60 | Polished Chrome |
| EN-DE82PC/40 | 8 | 4000 | 640 | 80 | 60 | Polished Chrome |
| EN-DE82SN/30 | 8 | 3000 | 610 | 76.25 | 60 | Satin Nickel |
| EN-DE82SN/40 | 8 | 4000 | 640 | 80 | 60 | Satin Nickel |
| EN-DE82W/30 | 8 | 3000 | 610 | 76.25 | 60 | White |
| EN-DE82W/40 | 8 | 4000 | 640 | 80 | 60 | White |

Compliance & Approvals:



Accessories:

| SKU Code | Description |
|-------------|----------------------------------|
| AU-FRLM10EM | 3 Hour Maintained Emergency Pack |

Warranty:

This product has a guarantee period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.