DATASHEET



Code: 742XLEDITB100

Hartland | HARTLAND RANGE | LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmers


Product Image



٠.		٠						
۱,	v	ı	r	ı	r	١	$\boldsymbol{\alpha}$	
v	v	ı		ı		ı	ч	
							J	



Dimensions



Insert Type	2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer				
Insert Colour	Satin Steel				
EAN13 Barcode	5017504079314				
Commodity Code	85365015				
Luckins TSI	403373648				
Dimensions(Nominal)	Single: Height = 88.0mm Width = 88.0mm Depth = 5.0mm				
Weight	155 GR				
Switched Poles	Single				
Current Rating	0.3A Per Gang				
Voltage	230V AC				
Maximum Load	5-70W Per Gang				
Mains Frequency	50Hz				
IP Rating	IP2XD				
Terminal Capacity 1	2X1mm²				
Terminal Capacity 2	2X1.5mm²				
Earth Terminal Capacity 1	5x1mm²				
Earth Terminal Capacity 2	4X1.5mm²				
Earth Terminal Capacity 3	3X2.5mm²				
Earth Terminal Capacity 4	1X4mm² Multi-Strand				
Earth Terminal Capacity 5	1X6mm²				
Product Class 1	Face plate muct be earthed				
Ambient Operating Temperature	-5°C to +40°C				
Recommended Location	Internal Use Only				
Maximum Installation Altitude	2000m				
Standard/Approval	BS EN 60669-2-1				
Additional Notes	Trailing Edge & Leading Edge Dimmer				

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of of certain finishes. This datasheet was expected in 2/12/2023 4/42-50 PM EX.OF.