

**PERFORMANCE+ DOWNLIGHT 245MM CUTOUT 1870LM 22W 3000K
NON-DIMM 85LM/W IP20 WHITE**

ILD245F007



The Integral LED 22W Watt Downlight delivers a warm white light and equivalent light output to traditional compact fluorescent. It incorporates a Polycarbonate diffuser and excellent thermal management to ensure a consistent light, long life and minimal maintenance. Ideal for commercial offices and buildings, retail premises and airports. A constant current non dimmable LED Driver is included as standard in this product. All Integral LED drivers and downlights benefit from our simple click and lock connectivity system.

Details

Quick Order Code:	286343
Barcode:	5055788232780
Category:	Downlights
Range Name:	Performance+
Product Type:	LED Downlights
Product Body Finish:	Matt white
Market Segment:	Commercial indoor
Warranty (Years):	5
CE RoHS:	Yes

Physical Data

Product Depth (mm):	62
Product Weight (g):	795
Optic:	Polycarbonate diffuser
Material:	Aluminium, Polycarbonate
Overall diameter (mm):	265
Construction:	Extruded Aluminium heat-sink and body, Polycarbonate sheet diffuser
Cut Out Diameter (mm):	245
Luminaire Fixing:	Recess mounted
Placement / Application:	Indoor, General Lighting

Electrical Data

Power (W):	22
Power Consumption (w):	22
Power Factor:	0.9

Wattage equivalent (W):	52
Dimming:	Non-Dimmable
Driver Included:	Yes
Electric Current:	AC
EN:	EN-60598
LVD Certified:	Yes

Light Data

Luminous Flux in Lumens (lm):	1870
Luminous efficacy (lm/W):	85
Peak Intensity (Cd):	668
Correlated Colour Temperature (CCT) (K):	3000
Colour Temperature:	3000K - Warm White
Colour Temperature Name:	Warm White
Beam Angle:	90
Colour Rendering Index (CRI):	80
Frequency Range (Hz):	50/60
Instant on (Less than 1 second):	Yes
LED Size (mm):	2835
LED Type:	Surface mounted device (SMD)
Lifetime (hours):	35000
Switching Cycles:	20000

Environment

EN:	EN-60598
LVD Certified:	Yes
CE RoHS:	Yes
Hg 0% (Mercury Free):	Yes
IP Rating (Ingress Protection):	IP20
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	40

Packaging

Package Weight (g):	900
Package Length (mm):	268
Package Width (mm):	268
Package Depth (mm):	80