# Classic Globe (GLS) 12W (75W) 2700K 1060Im B22 Dimmable Frosted Lamp

Partcode: ILGLSB22DC024 / Page: 1



As LED products produced using new technologies are used with old dimmer technology, achieving effective and smooth dimming can be challenging. For this dimmable lamp we have tested, and recommend, the dimmer detailed in the specification below.

This 12W retro-fit Integral LED Classic Globe (GLS) (large bayonet base) delivers a dimmable, warm light and brightness, similar to a 75W filament bulb. It features high output LEDs, an anti-glare refractor, all finished in an aluminium and plastic, thermally efficient body. Ideal for living rooms, hallways and kitchens.

# **Product Details**

Partcode: ILGLSB22DC024 Check Code: 854158 Range Name: Mensae Placement / Application: Indoor, General Lighting Product Type: GLS Warranty: 2 Years CE / RoHS: Yes

# **Physical Data**

Lamp Base: B22 Base Type: Bayonet cap Base Colour: Matt white Globe Type: Classic Globe (GLS) Globe Finish: Frosted Material: Plastic, Polycarbonate, Nickel plated brass Construction: Aluminium and Plastic heat-sink, Injection moulded diffuser

# www.integral-led.com

# integral LED

Partcode: ILGLSB22DC024 / Page: 2

### **Physical Data**

Length: 124mm Width: 60mm Weight (Unpackaged Single Unit): 150g Lamp or Luminaire Shape: Round

### **Electrical Data**

Voltage Range: 220-240V Power Consumption: 12.0 Watts Driver included: Yes Driver IC Manufacturer: Power Integrations (PI) Electric Current: AC Ampage: 58.00mA Frequency Range: 50 Hz Power Factor: >=0.50 Wattage Equivalent: 75 Watts Dimming: Dimmable with compatible dimmers LVD Certified: Yes EN: EN-62560

# **Light Data**

Lumens: 1,060lm Lumens per Watt: 88.0lm/W Beam Angle: 240° Correlated Colour Temperature (CCT): 2,700k Colour Temperature: Warm Colour Rendering Index (CRI): >=80 LED Type: Surface mounted device (SMD) Instant on - Less than 1 second: Yes Lifetime: 15,000 hrs Switching Cycles: >12,500 X

# www.integral-led.com



Partcode: ILGLSB22DC024 / Page: 3

#### **Environmental**



Energy Rating: A+ Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

# Packaging



EAN Barcode (unit of 1): 5055788209911 Packaged Weight (Unit of 1): 190g Length (unit of 1): 140mm Width (unit of 1): 68mm Depth (unit of 1): 68mm **Outer packaging info available on website** 

Product data last updated on: Thursday, October 25, 2018 - 15:32

#### www.integral-led.com