

# **Product Specification Sheet**

# GU10 Glass PAR16 4.7W (50W) 2700K 390lm Non-Dimmable Lamp

Partcode: ILGU10NC083 / Page: 1



The glass body and cleverly engineered surface mounted LEDs of the Integral LED Glass GU10 range give them an attractive look that is very similar to traditional halogen lamps.

These GU10 lamps will retrofit easily into existing fittings and provide significant energy savings and longer lifetime than the halogen lamps they are designed to replace.

#### **Product Details**

Partcode: ILGU10NC083 Check Code: 324099

Range Name: Glass

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: GU10 Warranty: 2 Years CE / RoHS: Yes

### **Physical Data**

Lamp Base: GU10 PAR16

Base Type: GU10

Globe Finish: Dichroic look

Spot Type: SMD with "COB like effect"

Optic: Designed to give a Halogen look

Material: Glass

Construction: Glass body and "fly eye" difuser lens



# **Product Specification Sheet**

Partcode: ILGU10NC083 / Page: 2

### **Physical Data**

Length: 54mm Width: 50mm

Weight (Unpackaged Single Unit): 50g Lamp or Luminaire Shape: Round

Lamp Fixing: Downlight

#### **Electrical Data**

Voltage Range: 220-240V

Power Consumption: 4.7 Watts

Driver included: Yes

Driver IC Manufacturer: SM7307

Electric Current: AC Ampage: 42.00mA

Frequency Range: 50/60 Hz

Power Factor: >=0.40

Wattage Equivalent: 50 Watts

Dimming: Non-dimmable

LVD Certified: Yes EN: EN-62560

### **Light Data**

Useful Lumens: 345lm (Rated luminous flux in a 90° cone)

Lumens: 390lm

Lumens per Watt: 83.0lm/W

Peak Intensity: 850Cd

Beam Angle: 36º

Correlated Colour Temperature (CCT): 2,700k

Colour Temperature: Warm

Colour Rendering Index (CRI): >=80

LED Manufacturer: Seoul

LED Type: Surface mounted device (SMD)

Instant on - Less than 1 second: Yes

Lifetime: 15,000 hrs


Switching Cycles: >7,500 X



# **Product Specification Sheet**

Partcode: ILGU10NC083 / Page: 3

#### **Environmental**



Energy Rating: A+

Lowest Operating Temperature: -20 degrees

Maximum Operating Temperature: 40 degrees

IP (Ingress Protection) Rating: IP20

Hg 0% (Mercury Free): Yes

## **Packaging**

EAN Barcode (unit of 1): 5055788230595

Packaged Weight (Unit of 1): 61g

Length (unit of 1): 60mm Width (unit of 1): 55mm Depth (unit of 1): 55mm

Outer packaging info available on website

Product data last updated on: Monday, August 7, 2017 - 14:39