MR16 Glass GU5.3 5.2W (37W) 4000K 450Im Dimmable Lamp

Partcode: ILMR16DE032 / Page: 1



The glass body and cleverly engineered surface mounted LEDs of the Integral LED Glass MR16 range give them an attractive look that is very similar to traditional halogen lamps.

These MR16 lamps will retrofit easily into existing fittings and provide significant energy savings and longer lifetime than the halogen lamps they are designed to replace.

Product Details

Partcode: ILMR16DE032 Check Code: 334593 Range Name: Glass Placement / Application: Indoor, General Lighting Market Segment: Commercial indoor, Residential indoor Product Type: MR16 Warranty: 2 Years CE / RoHS: Yes

Physical Data

Base Type: GU5.3 Spot Type: SMD with "COB like effect" Optic: Designed to give a Halogen look Material: Aluminium, Glass Construction: Glass with Aluminium heat-sink, Injection moulded diffuser

integral LED

Partcode: ILMR16DE032 / Page: 2

Physical Data

Length: 44mm Width: 50mm Weight (Unpackaged Single Unit): 43g Lamp or Luminaire Shape: Round Lamp Fixing: Downlight

Electrical Data

Voltage Range: 12V Power Consumption: 5.2 Watts Driver included: No, needs 12V AC Transformer Driver IC Manufacturer: IWATT Electric Current: AC Ampage: 460.00mA Frequency Range: 50 Hz Power Factor: >=0.90 Wattage Equivalent: 37 Watts Dimming: Dimmable Compatible Dimmer(s): Varilight JQP401W LVD Certified: Yes EN: EN-62560

Light Data


Useful Lumens: 380lm (Rated luminous flux in a 90° cone) Lumens: 450lm Lumens per Watt: 87.0lm/W Peak Intensity: 650Cd Beam Angle: 36° Correlated Colour Temperature (CCT): 4,000k Colour Temperature: Cool White Colour Rendering Index (CRI): >=80 LED Manufacturer: Seoul LED Type: Surface mounted device (SMD) LED Size: 2835 Instant on - Less than 1 second: Yes Lifetime: 25,000 hrs Switching Cycles: >12,500 X

www.integral-led.com



Partcode: ILMR16DE032 / Page: 3

Environmental



Energy Rating: A+ Lowest Operating Temperature: -20 degrees Maximum Operating Temperature: 40 degrees IP (Ingress Protection) Rating: IP20 Hg 0% (Mercury Free): Yes

Packaging

EAN Barcode (unit of 1): 5055788231202 Packaged Weight (Unit of 1): 63g Length (unit of 1): 60mm Width (unit of 1): 55mm Depth (unit of 1): 55mm **Outer packaging info available on website**

Product data last updated on: Monday, August 7, 2017 - 14:39

www.integral-led.com