



## DATASHEET



### SPIKE5A

### 230V IP65 6W LED Wall/Spike Spotlight

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	SPIKE5A
DESCRIPTION	230V IP65 6W LED Wall/Spike Spotlight
NET WEIGHT (KG)	0.78
FINISH	Black
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 95 Length - 87 Projection - 128 Overall Height - 340 Spike Length - 210
CONSTRUCTION	Construction - Die-cast aluminium Construction 2 - & 304 stainless steel
CLASS	I
IP RATING	IP65
WATTAGE (W)	6
LAMP TECHNOLOGY	CoB LED
LAMP INCLUDED	Yes
LUMENS (LM)	380
LUMENS LIGHT SOURCE ONLY (LM)	560
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	90.38
CIRCUIT WATTAGE (W)	6.2
CCT	3000K
LIGHT COLOUR	Warm White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.05
DISPLACEMENT FACTOR	>0.9
SVM	0.004
PST-LM	0.21
BEAM ANGLE (DEGREES)	35

LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-25~35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	2
CABLE TYPE	3 x 1.0mm <sup>2</sup> H05RN-F
DRIVER	DRIVER TYPE - Constant Current OUTPUT VOLTAGE - 12-21V OUTPUT CURRENT - 300mA ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 50°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	2year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270800432

Date Created: 09/08/2022 09:11

