Knightsbridge








230V IP20 30W T8 6ft LED Tube 4000K

www.mlaccessories.co.uk



FINISHWhiteDIFFUSEROpalDIMENSIONS (MM)Diameter - 26 Length - 1778CONSTRUCTIONConstruction - Polycarbonate Construction - Polycarbonate Construction 2 - & aluminiumP RATINGIP20NATTAGE (W)30LAMP TECHNOLOGYLEDLAMP BASET8LUMENS (LM)3350LUMENS (LM)5%EFFICACY (LMW)116.3CT4000KCGT4000KCRI>80SDCM<6RUNNING CURRENT (A)0.135DISPLACEMENT FACTOR>0.9SW0.035LIFE SPAN (HRS)30,000DIMMABLENoOPERATING TEMPERATURE-20~50°C	MLA PART CODE	T8LED6
DIFFUSER Opal DIMENSIONS (MM) Diameter - 26 Length - 1778 CONSTRUCTION Construction - Polycarbonate Construction 2 - & aluminium P RATING IP20 WATTAGE (W) 30 LAMP TECHNOLOGY LED LAMP BASE T8 LUMENS (LM) 3350 LUMENS (LM) 3350 LUMENS (LMW) 116.3 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <66 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SW 0.035 LIFE SPAN (HRS) 30,000 LIFE SPAN (HRS) 20,000 DIMMABLE No	DESCRIPTION	230V IP20 30W T8 6ft LED Tube 4000K
DIMENSIONS (MM) Diameter - 26 Length - 1778 CONSTRUCTION Construction - Polycarbonate Construction 2 - & aluminium P RATING IP20 MATTAGE (W) 30 LAMP TECHNOLOGY LED LAMP BASE T8 LUMENS (LM) 3350 LUMENS (LM) 3350 LUMENS (LM) 6% EFFICACY (LMW) 116.3 CIRCUIT WATTAGE (W) 28.81 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.035 LIFE SPAN (HRS) 30,000 LIFE SPAN (HRS) 20,000 DIMMABLE No DPERATING TEMPERATURE -20~50°C	FINISH	White
Length - 1778CONSTRUCTIONConstruction - Polycarbonate Construction 2 - & aluminiumP RATINGIP20WATTAGE (W)30LAMP TECHNOLOGYLEDLAMP BASET8LUMENS (LM)3350LUMENS (LM)116.3CCT4000KCIGHT COLOURCool WhiteCRI>80SDCM<6	DIFFUSER	Opal
Construction 2 - & aluminiumP RATINGIP20WATTAGE (W)30LAMP TECHNOLOGYLEDLAMP BASET8LUMENS (LM)3350LUMEN TOLERANCE5%EFFICACY (LM/W)116.3CIRCUIT WATTAGE (W)28.81CCT4000KLIGHT COLOURCool WhiteCRI>80SDCM<6RUNNING CURRENT (A)0.135DISPLACEMENT FACTOR>0.9SVM0.839PST-LM0.035LIFE SPAN (HRS)30,000DIMMABLENoODPERATING TEMPERATURE-20~50°C	DIMENSIONS (MM)	
AMATTAGE (W) 30 LAMP TECHNOLOGY LED LAMP BASE T8 LUMENS (LM) 3350 LUMEN TOLERANCE 5% EFFICACY (LM/W) 116.3 CIRCUIT WATTAGE (W) 28.81 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.035 LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No ODPERATING TEMPERATURE -20~50°C	CONSTRUCTION	Construction - Polycarbonate Construction 2 - & aluminium
LAMP TECHNOLOGY LED LAMP BASE T8 LUMENS (LM) 3350 LUMEN TOLERANCE 5% EFFICACY (LM/W) 116.3 CIRCUIT WATTAGE (W) 28.81 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.839 PST-LM 0.035 LIFE SPAN (HRS) 30,000 LTFE SPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	IP RATING	IP20
LAMP BASE T8 LUMENS (LM) 3350 LUMEN TOLERANCE 5% EFFICACY (LM/W) 116.3 CIRCUIT WATTAGE (W) 28.81 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.035 LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	WATTAGE (W)	30
LUMENS (LM) 3350 LUMEN TOLERANCE 5% EFFICACY (LM/W) 116.3 CIRCUIT WATTAGE (W) 28.81 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.035 LIFE SPAN (HRS) 30,000 LIFE SPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	LAMP TECHNOLOGY	LED
LUMEN TOLERANCE5%EFFICACY (LM/W)116.3CIRCUIT WATTAGE (W)28.81CCT4000KLIGHT COLOURCool WhiteCRI>80SDCM<6RUNNING CURRENT (A)0.135DISPLACEMENT FACTOR>0.9SVM0.839PST-LM0.035LIFE SPAN (HRS)30,000LTRESPAN (HRS)20,000DIPRATING TEMPERATURE-20~50°C	LAMP BASE	Т8
EFFICACY (LM/W) 116.3 CIRCUIT WATTAGE (W) 28.81 CCT 4000K LIGHT COLOUR Cool White CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.839 PST-LM 0.035 LIFE SPAN (HRS) 30,000 LIFE SPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	LUMENS (LM)	3350
CIRCUIT WATTAGE (W)28.81CCT4000KLIGHT COLOURCool WhiteCRI>80SDCM<6RUNNING CURRENT (A)0.135DISPLACEMENT FACTOR>0.9SVM0.839PST-LM0.035LIFE SPAN (HRS)30,000LIFESPAN (HRS)20,000DIMMABLENoOPERATING TEMPERATURE-20~50°C	LUMEN TOLERANCE	5%
CCT4000KLIGHT COLOURCool WhiteCRI>80SDCM<6RUNNING CURRENT (A)0.135DISPLACEMENT FACTOR>0.9SVM0.839PST-LM0.035LIFE SPAN (HRS)30,000LIFE SPAN (HRS)20,000DIMMABLENoODERATING TEMPERATURE-20~50°C	EFFICACY (LM/W)	116.3
LIGHT COLOURCool WhiteCRI>80SDCM<6RUNNING CURRENT (A)0.135DISPLACEMENT FACTOR>0.9SVM0.839PST-LM0.035LIFE SPAN (HRS)30,000LIFE SPAN (HRS)20,000DIMMABLENoOPERATING TEMPERATURE-20~50°C	CIRCUIT WATTAGE (W)	28.81
CRI >80 SDCM <6 RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.839 PST-LM 0.035 LIFE SPAN (HRS) 30,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	сст	4000K
SDCM <6	LIGHT COLOUR	Cool White
RUNNING CURRENT (A) 0.135 DISPLACEMENT FACTOR >0.9 SVM 0.839 PST-LM 0.035 LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	CRI	>80
DISPLACEMENT FACTOR >0.9 SVM 0.839 PST-LM 0.035 LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	SDCM	<6
SVM 0.839 PST-LM 0.035 LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	RUNNING CURRENT (A)	0.135
PST-LM 0.035 LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	DISPLACEMENT FACTOR	>0.9
LIFE SPAN (HRS) 30,000 L70B50 LIFESPAN (HRS) 20,000 DIMMABLE No OPERATING TEMPERATURE -20~50°C	SVM	0.839
L70B50 LIFESPAN (HRS)20,000DIMMABLENoOPERATING TEMPERATURE-20~50°C	PST-LM	0.035
DIMMABLE No OPERATING TEMPERATURE -20~50°C	LIFE SPAN (HRS)	30,000
OPERATING TEMPERATURE -20~50°C	L70B50 LIFESPAN (HRS)	20,000
	DIMMABLE	No
	OPERATING TEMPERATURE	-20~50°C
NPUT VOLTAGE 230V 50Hz	INPUT VOLTAGE	230V 50Hz
WARRANTY 3year(s)	WARRANTY	3year(s)





Knightsbridge

BS EN 62560
China
Yes
5055832938651

Date Created: 27/07/2022 13:36







ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.