

Sirius Low Bay 100W 15000 lumens with emergency function

EL100SFLB3E



PRODUCT DATA

| | |
|------------------------|-------------|
| LUMENS (lm) | 15000lm |
| DIMMABLE | 1-10 |
| WATTAGE (W) | 100W |
| COLOUR TEMPERATURE (K) | 5000K |
| EMERGENCY | YES |
| WEIGHT (kg) | 3.6kg |
| BEAM ANGLE | 90° |
| CRI | >80 |
| REPLACEMENT FOR | 250W MH/SON |
| DIMENSIONS (mm) | φ260×175mm |
| PRODUCT TYPE | Low bays |
| EFFICIENCY (lm/w) | 150lm/W |
| RATED LIFETIME (hrs) | 50,000hrs |
| IP | 65 |
| WORKING ENVIRONMENT | 5°C to 30°C |
| WARRANTY | 5 |
| L70 RATING (hrs) | >80000 |


KEY FEATURES

Ideal for installations at height of 5-8 metres, the Sirius Low Bay 15000 lumen with emergency function is easy to install with flexible mounting options. It is fully compliant with emergency lighting regulation ensuring that when there is a power outage, it gives sufficient light for 3 hours from a battery unit. It comes with a dimmable driver as standard and Philips Lumiled chips to ensure high efficiency and reliability. Perfect for projects and installations of all sizes. The lumen output when the fitting is in emergency mode is 500lm.


COMMERCIAL APPLICATIONS

Warehouses, factories, sports arenas, sports halls, retail outlets

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

