

PRODUCT DATA SHEET

Hellion High Bay 150W 21000 lumens

EL150HFB





PRODUCT DATA

DIMMABLE 1-10 WATTAGE (W) 150W COLOUR TEMPERATURE (K) 5000K WEIGHT (kg) 7kg BEAM ANGLE 110×120° CRI >80 REPLACEMENT FOR 4x54W T5 high output DIMENSIONS (mm) 1090x322x60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20 WORKING ENVIRONMENT -35°C to 35°C	LUMENS (Im)	21000lm
COLOUR TEMPERATURE (K) 5000K WEIGHT (kg) 7kg BEAMANGLE 110×120° CRI >80 REPLACEMENT FOR 4×54W T5 high output DIMENSIONS (mm) 1090×322×60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	DIMMABLE	1-10
WEIGHT (kg) 7kg BEAM ANGLE 110×120° CRI >80 REPLACEMENT FOR 4x54W T5 high output DIMENSIONS (mm) 1090x322x60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	WATTAGE (W)	150W
BEAM ANGLE 110×120° CRI >80 REPLACEMENT FOR 4x54W T5 high output DIMENSIONS (mm) 1090x322x60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	COLOUR TEMPERATURE (K)	5000K
CRI >80 REPLACEMENT FOR 4x54W T5 high output DIMENSIONS (mm) 1090x322x60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	WEIGHT (kg)	7kg
REPLACEMENT FOR 4x54W T5 high output DIMENSIONS (mm) 1090x322x60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	BEAMANGLE	110x120°
DIMENSIONS (mm) 1090x322x60mm PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	CRI	>80
PRODUCT TYPE High bays EFFICIENCY (lm/w) 140lm/W RATED LIFETIME (hrs) 50,000hrs IP 20	REPLACEMENT FOR	4x54W T5 high output
EFFICIENCY(Im/w) 140Im/W RATED LIFETIME (hrs) 50,000hrs IP 20	DIMENSIONS (mm)	1090x322x60mm
RATED LIFETIME (hrs) 50,000hrs IP 20	PRODUCTTYPE	High bays
IP 20	EFFICIENCY(lm/w)	140lm/W
	RATED LIFETIME (hrs)	50,000hrs
WORKING ENVIRONMENT -35°C to 35°C	IP	20
	WORKING ENVIRONMENT	-35°C to 35°C
WARRANTY 5	WARRANTY	5


KEY FEATURES

An ideal replacement for MH or fluorescent Low Bays, the Hellion 21000 lumens is low glare with clear or frosted polycarbonate lenses, in-built emergency options housed in a lightweight and slimline, white, aluminium casing.


COMMERCIAL APPLICATIONS

Warehouse racking, manufacturing production, depots, airports, retails outlets, exhibition centres.

POLAR CURVE DIAGRAM



CONE DIAGRAM



DIMENSIONS

