



Product Code: CCA040

Description: 20A Double Pole Switch 'Water Heater' With Optional Flex Outlet

WATER HEATER	•	
General Information		
Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Rounded Profile	
Finish	Polar White	
Materials	Front Plate & Rocker Switch: Urea	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Bras	ss Internal Busbars: Formed Pressed Brass
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)		Ferminal Torque Value (Nm) 1.8
Terminal Capacity - Solid (mm ²)	3 x 2.5	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	Water Heater	
Flex Outlet Available	Yes	
Flex Outlet Location	Front of Plate F	Iex Outlet Dimension (mm) Ø10
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	
diagram Bare ear All white propertie propertie All produ envelope	hat the mains supply is isolated before c with the relevant product. th cables must always be covered with a moulded accessories are manufactured as to antimicrobial additives that inhibit the against enveloped and non-enveloped acts have been independently tested with	commencing installation and refer to the circuit appropriate sleeving and wired to the earth terminal. d using Urea Formaldehyde, which has similar inheren he growth of infectious diseases as well as anti-viral d viruses. th 99.9% of enveloped viruses and 92% of non- 9.9% kill rate across all four types of the strains of

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom T: +44 (0)1827 63454 | F: +44 (0)1827 63362 E: sales@scolmore.com | W: scolmore.com

Page 1 of 1 (18/02/22) Errors & Omissions excluded. Specification is subject to change without notice.