

Product Code: CSP033

Description: Smart Temperature & Humidity Sensor



General Information

Dimensions (mm)	37 (Dia.) x 11.6 (D)	
Finish	White	
Materials	Housing: Polycarbonate	Electronics: PCB & Electronic Components
Rated Voltage (DC)	3	
Battery Type	CR 2032 (Supplied)	
Battery Lifetime (Approx.)	1 Year (Dependent On Use)	
Protocol	Zigbee	Signal Transmission Frequency 2.4GHz
Temperature Accuracy (%)	±3	
Indicator Colour	Blue	
Ingress Protection	IP20	
Working Humidity	0%-100%RH (Non-condensing)	
Operational Temperature (°C)	-10 to +50	
Warranty (Years)	1	
Standards	BS EN 60950-1 BS EN 55035 BS EN 61000-3-2 BS EN 61000-3-3 BS EN 62311	

Additional Information	Control linked receivers through the ClickSmart+ app Send activation alerts to your phone
Components Supplied	Smart Temperature & Humidity Sensor, CR 2032 Battery, Reset Key, Instruction Manual
Installation Overview	Suitable for ceiling or wall mounting. Self-adhesive pad applied ready for installation.
Programming Information	With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Can be paired with hub via app.