

Product Code: CSP071

Description: Smart RGBW LED Tape Controller



General Information

Dimensions (mm)	46 (W) x 18 (H) x 115 (L)	
Finish	White	
Materials	Housing: Polycarbonate	Electronics: PCB & Electronic Components
Rated Voltage (DC)	12 to 24	
Resistive Load Rating (A)	8	
Termination Type	Screw	
Terminal Capacity - Solid (mm²)	1.5	
Terminal Capacity - Flex (mm²)	1.5	
Protocol	Zigbee	Signal Transmission Frequency 2.400 to 2.483GHz
Open Air Wireless Range (M)	<50	
Standby Current (mA)	50	
Indicator Colour	LED Strip Connected	
Ingress Protection	IP20	
Working Humidity	≤95%	
Operational Temperature (°C)	-20 to +45	
Warranty (Years)	3	
Standards	BS EN 62368-1 BS EN 62479 BS EN 50663 ETSI EN 301 489-1 ETSI EN 301 489-17 & EN 300 328 V2.2.2	

Additional Information Fits between the LED driver and LED strip
Powered by the LED driver output (12-24V DC)
Enables the control of white or RGBW LED strip

Components Supplied Smart RGBW LED Tape Controller, Instruction Manual

Installation Overview LED strip and controller powered by the LED driver installed
Wirelessly pairs to ClickSmart+ app

Programming Information With hub and app setup and controller wired and powered, press and hold the 'Reset' button for 5 seconds, the LED strip will start flashing to confirm in pairing mode. Can be paired with hub via app.