

**Product Code:** CSPGM2075PW

**Description:** Smart GridPro Scenario Switch



### General Information

<b>Dimensions (mm)</b>	24.5 (W) x 50 (H) x 22.5 (D)	
<b>Finish</b>	Polar White	
<b>Insert Colour</b>	Polar White	
<b>Materials</b>	Body & Insert: Nylon	Switch: Polycarbonate
<b>Rated Voltage (DC)</b>	3	
<b>Battery Type</b>	CR 2032 (Supplied)	
<b>Battery Lifetime (Approx.)</b>	300 Days (Dependent On Use)	
<b>Protocol</b>	Zigbee	<b>Signal Transmission Frequency</b> 2.4GHz
<b>Open Air Wireless Range (M)</b>	<50	
<b>Indicator Colour</b>	Blue	
<b>Minimum Back Box Depth (mm)</b>	25 (35 Flat Plate)	
<b>Ingress Protection</b>	IP20	
<b>Working Humidity</b>	0%-90%RH	
<b>Operational Temperature (°C)</b>	-5 to +40	
<b>Warranty (Years)</b>	2	

<b>Standards</b>	BS EN 62368-1 BS EN 62479 BS EN 50663 ETSI EN 301 489-1 ETSI EN 301 489-17 & EN 300 328 V2.2.2
------------------	--

**Components Supplied** Smart Scenario Switch, CR 2032 Battery, Reset Key, Instruction Manual

**Installation Overview** Utilises inserts and plates in the GridPro range  
Wireless pairs to ClickSmart+ app  
Single and multiple presses can be set to activate devices via the app "Tap To Run" setup

**Programming Information** With hub and app setup with sensor having battery installed, using the pin supplied press the reset button for five seconds and the sensor LED will start flashing. Must be paired with hub via app.